

CA615K



HEAT-RESISTANT LEATHER HIDE WELDER'S GLOVE / KEVLAR® SEWN

Ref. CA615K



Product specifications

High quality heat-resistant split leather (HR). Cuff with canvas lining. Kevlar® Technology sewn. American assembly. Length: 35 cm.

Top quality heat-resistant leather hide, thickness: 1.2 mm to 1.4 mm.

Lined hand : cotton fleece.

Cuff lined : cotton 300 g/m².

Kevlar® sewn.

COLOUR

Red

SIZE

10

Product Use - Risks



Heat



Wearing



Heavy industry

Certifications and Standards



PPE DIRECTIVE 89/686/EEC

EN420:2003 General requirements

EN388:2003 Protective gloves against mechanical Risks (Levels obtained on the palm)



- 3: Resistance to abrasion (from 1 to 4)
- 1: Resistance to cutting (from 1 to 5)
- 3: Resistance to tear (from 1 to 4)
- 3: Resistance to puncture (1 to 4)

EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)



- 4: Resistance to flammability (from 1 to 4)
- 1: Resistance to contact heat (from 1 to 4)
- 3: Resistance to convective heat (from 1 to 4)
- X: Resistance to radiant heat (from 1 to 4)
- 4: Resistance to small projections of molten metal (from 1 to 4)
- X: Resistance to large projections of molten metal (from 1 to 4)

EN12477:2001/A1:2005 Protective gloves for welders

- A: Welding - Other welding processes - less dexterity - Type A

References

| References | Bar code | COLOUR | SIZE |  |  |
|------------|---------------|--------|------|---|---|
| CA615K10 | 3295249021597 | Red | 10 | 60 | 12 |